



SECTION A-A

NOTES:

1. ALL CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION."
2. WHERE EXISTING CONCRETE IS TO BE REMOVED, IT SHALL FIRST BE SAWCUT AT THE NEAREST SCOREMARK.
3. BASE SHALL BE **CRUSHED MISC. BASE** PER "STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION"
4. "W" SHALL BE A MINIMUM OF 5' ON ARTERIAL & COLLECTOR STREETS, AND A MINIMUM OF 4' ON LOCAL STREETS.
5. FULL PARKWAY SIDEWALK, CONSTRUCTED PER STANDARD ST-5B, IS PERMITTED FOR MULTIPLE RESIDENTIAL ZONES WHICH FRONT ON ARTERIAL OR COLLECTOR STREETS.
6. NO SAWCUT ON CONTROL LINES.

NOTE:

NEW SIDEWALKS WILL REQUIRE CRUSHED MISCELLANEOUS BASE.
 SIDEWALKS (REPLACEMENT OF SIDEWALK) RECOMPACT EXISTING BASE MATERIAL.

CITY OF GARDENA

ENGINEERING DIVISION

TITLE:

RESIDENTIAL SIDEWALK

APP. BY:

[Signature] 12/16/98
 DATE

DESIGNED BY

DRAWN BY

CHECKED BY

A.W.D.

12/16/98

DWG.
 NO.

ST - 5A