


PLAN VIEW



NOTES:

- 1. ALL CONSTRUCTION SHALL BE IN CONFORMANCE WITH THE "SPPWC" LATEST EDITION.
- PCC SHALL BE 520-C-2500 PER "SPPWC" LATEST EDITION.
 CAB AND CMB TO 95 % RELATIVE COMPACTION AND 90 % SUBGRADE.
- EXISTING CONCRETE SHALL BE REMOVED TO THE NEAREST SCOREMARK.
- 5. DRIVEWAY INSTALLATION SHALL BE IN CONFORMANCE WITH THE DRIVEWAY POLICY OF THE DEPARTMENT OF PUBLIC WORKS (ST-1).
- 6. COARSE BROOM FINISH ON DRIVEWAY AND FINE HAIR BROOM FINISH ON SIDEWALK.
- 7. "W"=12' MIN. & 35' MAX. (OR AS APPROVED) AND "X"=3' MIN.
- 8. "V" DIMENSION SHALL BE 2' MIN. & ESTABLISHED IN FIELD BASED ON "Y" DEPTH REQUIRED (Y=0.30' MAX., ADJUST TO MATCH FIELD CONDITIONS). 9. ASPHALT AND CONCRETE TO BE REMOVED SHALL BE SAWCUT.
- 10. PLACE WEAKENED PLANE JOINTS (WPJ) EVENLY SPACED AT 10' O.C. MAX.
- 11. WIDTH OF 24" OF AC/AB TO BE R&R WHEN REPLACING C&G PORTION OF DRIVEWAY.

DWG NTS

	CITY OF GARDENA DEPARTMENT OF PUBLIC WORKS	APP. BY:	n Rigg		9/16	/2024	
	TITLE: COMMERCIAL DRIVEWAY		() ()	() ()		DATE	
١		DESIGNED BY	KK	09/24	DWG.		
	•	DRAWN BY	KK	09/24	NO.	ST-2	
		CHECKED BY	KK	09/24	NO.		